

NOCTIS LUX 4

SLI029077NW_CZUJNIK_PW

Floodlight NOCTIS LUX 4, with a power of 50 W. It has a high IP44 rating, making it ideal for use in areas of high humidity. IK07 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.

IP44

IK07



Power	50 W
Luminous flux*	4300 lm (120°)
Colour of light	Neutral white
IK	07

Voltage	230 V
Colour temperature	4000 K
Beam angle	100 °
Degree of protection (IP)	IP44

Technical data

Code	SLI029077NW_CZUJNIK_PW
Power	50 W
Nominal current	215 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4300 lm (120°)
Luminous flux**	4300 lm (360°)
Lamp efficacy	86 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	176x221x53 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC
Other	PIR motion sensor ,

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	420 pcs.
Gross weight (1 pcs.)	0.544 kg

Related documents

 User manual Declaration of Conformity

