


NYMPHEA OPTIMA BLACK CCT

SLI031051CCT_PW

Plafond NYMPHEA OPTIMA BLACK CCT with the possibility of changing the light color (CCT), with a power of 65 W, high light efficacy 120 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000 / 4000 / 6000K, we can adjust the light color depending on our needs and preferences

CCT



Power	65 W	Voltage	230 V
Luminous flux*	7800 lm (360°)	Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI031051CCT_PW
Power	65 W
Nominal current	305 mA
Voltage	230 V
Energy consumption	65 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.95
Useful luminous flux*	7800 lm (360°)
Luminous flux**	5850 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Lifespan	17000 h
Housing material	Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	600x50 mm
For use	Inside
Application	Inside
Made in	PRC
Other	Light color change function 3000K / 4000K / 6000K ,

Logistics data

Bulk packaging	5 pcs.
Gross weight (1 pcs.)	2.45 kg

Related documents

 User manual Declaration of Conformity

