

ALGINE BACKLIGHT

SLI035061CW_PW

LED panel ALGINE BACKLIGHT, with a power of 40 W, high light efficacy 115 lm/W. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	40 W	Voltage	230 V
Luminous flux*	4600 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI035061CW_PW
Power	40 W
Nominal current	182 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4600 lm (360°)
Luminous flux	3600 lm (360°)
Lamp efficacy	115 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	3 years
Lifespan	26000 h
(On/Off)	15000
Housing material	aluminum/steel
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	620x620x28 mm
Mounting hole	590x590 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Certified by the National Institute of Hygiene	Yes
Made in	PRC

Logistics data

Bulk packaging	5 pcs.
Quantity per pallet	90 pcs.
Gross weight (1 pcs.)	1.8 kg


*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity