

SLI035082CCT_PW_IP44

ALGINE PANEL BACKLIGHT 26W/36W/46W CCT 230V 90DEG IP44 UGR19 600X600X34MM WHITE 5 YW



Power	26 / 36 / 46 W	Voltage	230 V
Luminous flux*	6300 lm (360°)	Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT	Beam angle	90 °
UGR	<19	Degree of protection (IP)	IP44

Technical data


Logistics data

Code	SLI035082CCT_PW_IP44
Power	26 / 36 / 46 W
Nominal current	200 mA
Voltage	230 V
Energy consumption	46 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.950000
Useful luminous flux*	6300 lm (360°)
Luminous flux	3120 / 4320 / 5520 lm (360°)
Lamp efficacy	137 lm/W
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	90 °
UGR	<19
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum / Plastic
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	595x595x34 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	DIP SWITCH adjustable power of luminaire ,

*applies to the LED source used

Related documents



 Declaration of Conformity