

SLI035088NW_PW_M

ALGINE PANEL BACKLIGHT 40W NW 230V 120ST IP40 600X600X32 BIAŁY 5LAT MESH



| | | | |
|---------------------------|-----------------------|--------------------|---------------|
| Power | 40 W | Voltage | 230 V |
| Luminous flux* | 4650 lm (360°) | Colour temperature | 4000 K |
| Colour of light | Neutral white | Beam angle | 120 ° |
| Degree of protection (IP) | IP40 | | |


Technical data

Logistics data

| | |
|--|--|
| Code | SLI035088NW_PW_M |
| Power | 40 W |
| Nominal current | 180 mA |
| Voltage | 230 V |
| Energy consumption | 40 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 4650 lm (360°) |
| Luminous flux | 4000 lm (360°) |
| Lamp efficacy | 116 lm/W |
| Colour temperature | 4000 K |
| Colour of light | Neutral white |
| Beam angle | 120 ° |
| RA | >80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | MESH |
| Working temperature range | 20 / +40 ° |
| Warranty | 5 years |
| Lifespan | 50000 h |
| (On/Off) | 25000 |
| Housing material | Aluminum / Plastic |
| Degree of protection (IP) | IP40 |
| Colour | White |
| Dimension (AxBxC) | 595x595x32 mm |
| For use | Inside |
| Assembly method | On the ceiling, Recessed |
| Application | INT |
| Certified by the National Institute of Hygiene | Yes |
| Made in | PRC |
| Other | montaż ramka 70 mm lub sufit armstrong , |
| Catalogue number | SLI035088NW_PW_M , |

*applies to the LED source used

Related documents


 Declaration of Conformity