

# ALLDAY BASIC 3CCT

SLI047305CCT\_PW

ALLDAY BASIC 40W 3CCT 230V 90DEG IP20 1203x42x37mm BLACK PR UGR19 5Y WARRANTY



|                 |                       |                           |                             |
|-----------------|-----------------------|---------------------------|-----------------------------|
| Power           | <b>40 W</b>           | Voltage                   | <b>230 V</b>                |
| Luminous flux*  | <b>5000 lm (360°)</b> | Colour temperature        | <b>2700 / 4000 / 6000 K</b> |
| Colour of light | <b>CCT</b>            | Beam angle                | <b>90 °</b>                 |
| UGR             | <b>UGR&lt;19</b>      | Degree of protection (IP) | <b>IP20</b>                 |

## Technical data

|                              |  |
|------------------------------|--|
| Code                         | SLI047305CCT_PW  |
| Power                        | 40 W   |
| Nominal current              | 175 mA   |
| Voltage                      | 230 V  |
| Energy consumption           | 40 kWh/1000h   |
| Frequency                    | 50HZ Hz  |
| Protection class             | I  |
| Power supply included        | Yes  |
| Power factor                 | 0.950000   |
| Useful luminous flux*        | 5000 lm (360°)   |
| Luminous flux                | 4000 lm (360°)   |
| Lamp efficacy                | 125 lm/W   |
| Colour temperature           | 2700 / 4000 / 6000 K                                   |
| Colour of light              | CCT  |
| Beam angle                   | 90 °   |
| UGR                          | <19  |
| RA                           | 80   |
| Light source included        | Yes  |
| Uniformity of color SDCM max | 5  |
| Dimmable                     | No   |
| Working temperature range    | 20 / +40 °   |
| Warranty                     | 5 years  |
| Lifespan                     | 50000 h  |
| (On/Off)                     | 30000  |
| Housing material             | Aluminum   |
| Degree of protection (IP)    | IP20   |
| Colour                       | Czarny   |
| Dimension (AxBxC)            | 1203x42x37 mm  |
| For use                      | Inside   |
| Assembly method              | On the ceiling, Suspended                              |
| Application                  | Inside   |
| Made in                      | PL   |
| Other                        | Light color change function<br>2700K / 4000K / 6000K , |


## Logistics data

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 15 pcs.  |
| Quantity per pallet   | 450 pcs. |
| Gross weight (1 pcs.) | 0.91 kg  |

\*applies to the LED source used

## Related documents



 User manual



 Declaration of Conformity

