

ALLDAY BASIC 3CCT

SLI047318CCT_PW

ALLDAY BASIC 30W/40W/50W 3CCT 230V 90DEG IP20 1503x42x37mm WHITE PR UGR19 5Y WARRANTY



Power	30W/40W/50W W	Voltage	230 V
Luminous flux*	6250 lm (360°)	Colour temperature	2700/4000/6000 K
Colour of light	CCT	Beam angle	90 °
UGR	UGR<19	Degree of protection (IP)	IP20

Technical data

Code	SLI047318CCT_PW
Power	30W/40W/50W W
Nominal current	220 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.950000
Useful luminous flux*	6250 lm (360°)
Luminous flux	3000/4000/5000 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	2700/4000/6000 K
Colour of light	CCT
Beam angle	90 °
UGR	<19
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	30000
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	1503x42x37 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	Inside
Made in	PL
Other	Light color change function 2700K/4000K/6000K ,

Logistics data

Bulk packaging	15 pcs.
Quantity per pallet	315 pcs.
Gross weight (1 pcs.)	1.237 kg

*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity