

GRID S

WLD+20013_CCT



Power	12 W	Voltage	230 V
Colour temperature	2700 / 3300 / 4000 K	Colour of light	CCT
Beam angle	40 °	UGR	<19
Degree of protection (IP)	IP20		

Technical data

Logistics data

Code	WLD+20013_CCT
Power	12 W
Nominal current	65 mA
Voltage	230 V
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.88
Useful luminous flux*	1200 lm (360°)
Luminous flux**	550 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	1200 cd
Colour temperature	2700 / 3300 / 4000 K
Colour of light	CCT
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	222x26x60 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PRC
Other	CCT ,

Bulk packaging 32 pcs.

Related documents

 User manual Declaration of Conformity

