

## **LED AR111 GU10**

W0J+16896

LED source LED AR111 GU10 20 W with the popular GU10 mount. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. Narrow beam angle 30° gives directional light so that selected objects or surfaces can be better exposed.





Power 20 W

Luminous flux\*\* 1800 lm (360°)

Colour of light **WW** 

Socket **GU10** 

Voltage 230 V

Colour temperature 2700 K

Beam angle 30 °

## www.spectrumled.pl



## Technical data Logistics data

Code **W0J+16896** 

Power 20 W

Nominal current 150 mA

Voltage 230 V

Energy efficiency class **F** 

Energy consumption 20 kWh/1000h

Frequency 50HZ Hz

Power supply included +

Power factor **0.6** 

Useful luminous flux\* 1600 lm (90°) Luminous flux\*\* 1800 lm (360°) Lamp efficacy 80 lm/W

Luminous intensity 4600 cd

Colour temperature 2700 K

Colour of light WW

Beam angle 30°

RA **90** 

Uniformity of color SDCM max 5

Dimmable No

Working temperature range -20 / +40 °

Lifespan **50000 h** 

Socket GU10

Colour Black

Dimension (AxBxC) 111x78 mm

For use Inside

Application INT

Made in **PRC** 

Bulk packaging 50 pcs. Quantity per pallet 1200 pcs.

Gross weight (1 pcs.) 0.16 kg



